## **DATA SHEET**

## Three Phase Induction Motor - Squirrel Cage



Customer

Product line : Rolled Steel NEMA Premium Efficiency

Three-Phase

Product code: 13733399

Catalog #:

01018ET3EBM215TC-S

: 27s (cold) 15s (hot)

Frame : 213/5TC : 10 HP (7.5 kW)

Output Poles Frequency Rated voltage Rated current L. R. Amperes

: 60 Hz : 230/460 V : 24.4/12.2 A : 171/85.4 A LRC : 7.0x(Code H) No load current : 11.1/5.54 A Rated speed : 1760 rpm Slip : 2.22 %

Rated torque : 29.8 ft.lb Locked rotor torque : 250 % Breakdown torque : 300 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 1.07 sq.ft.lb Design

Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method

Mounting

Locked rotor time

: IP55 : IC411 - TEFC : F-1 : Both (CW and CCW)

: 80 K

: Cont.(S1) : -20°C to +40°C

: 1000 m.a.s.l.

Rotation<sup>1</sup> Noise level<sup>2</sup> : 60.0 dB(A) Starting method : Direct On Line : 169 lb

Approx. weight<sup>3</sup>

Non drive end

6206 ZZ

Without Bearing Seal

25% 50% 75% 100% Foundation loads Output 90.2 91.7

Efficiency (%) 91.0 91.0 Max. traction : 421 lb : 589 lb Power Factor 0.41 0.78 0.84 0.67 Max. compression

Drive end

6208 ZZ

Bearing type Sealing

V'Ring Lubrication interval Lubricant amount

Mobil Polyrex EM

Notes:

Lubricant type

USABLE @208V 27.0A SF 1.00 SFA 27.0A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

, ,					
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	29/03/2024	1		1/2	

## DATA SHEET



Brake information  Voltage: 208-230/460/190/380 V Brake Torque: 50 2 ft.lb  Rev. Changes Summary Performed Checked Date  Performed by	Three Phase Induction Motor - Squirrel Cage								
Voltage: 208-230/460/190380 V Brake Torque: 50.2 ft.lb  Rev. Changes Summary Performed Checked Date  Performed by	Customer	:							
Voltage: 208-230/480/190380 V Brake Torque: 50.2 ft.lb  Rev. Changes Summary Performed Checked Date  Performed by									
Performed by	Voltage: 208-230 Brake Torque: 50	0/460//190/380 V 0.2 ft.lb	Brake informat	ion					
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by									
Performed by	Rev.		Changes Summary	Performed	Checked	Date			
Cinecked by   Page Pavision	Performed by Checked by				Page	Revision			

2/2

29/03/2024

Date