## **DATA SHEET**

#### Three Phase Induction Motor - Squirrel Cage



Three I hase induction wotor oquirer oage						
Customer	:					
Product line	: W21 Phase		n Proof Hig	h Efficiency	Three- Product code :	12823465
Frame		: 254TC			Locked rotor time	: 48s (cold) 27s (hot)
Output			(11 kW)		Temperature rise	: 80 K
Poles		: 4			Duty cycle	: Cont.(S1)
Frequency		: 60 Hz			Ambient temperature	: -20°C to +40°C
Rated voltage		: 230/46			Altitude	: 1000 m.a.s.l.
Rated current		: 36.2/1			Protection degree	: IP55
L. R. Amperes		: 232/1′			Cooling method	: IC411 - TEFC
LRC			Code G)		Mounting	: W-6
No load current		: 14.6/7			Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed		: 1760 ı : 2.22 %			Noise level <sup>2</sup>	: 69.0 dB(A)
Slip		: 2.22 % : 44.8 ft			Starting method Approx. weight <sup>3</sup>	: Direct On Line : 330 lb
Rated torque Locked rotor torqu	10	: 250 %			Approx. weight	. 330 ib
Breakdown torque		: 250 %				
Insulation class	•	: F	)			
Service factor		: 1.15				
Moment of inertia	(J)	: 2.38 s	a.ft.lb			
Design	(-)	: B	9			
Output		50%	75%	100%	Foundation loads	
Efficiency (%)	90.0 86.9				Max. traction	: 406 lb
	88.0 88.8					
Power Factor				0.84 0.85	Max. compression	: 736 lb
	0.46 0.43	0.70 0.67	0.80 0.78	0.84 0.83		
			<u>Drive</u>		Non drive end	
Bearing type		:	6309 2		6209 2RS C3	
Sealing		:	Oil S	Seal	Lip Seal	
Lubrication interva	ıl	:	-		-	
Lubricant amount		:	-			
Lubricant type		:		Мо	bil Polyrex EM	
Notes:						

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

, ,						
Rev.	Changes Summary		Performed	Checked	Date	
Performed by						
Checked by					Page	Revision
Date	27/03/2024	1			1/2	

# DATA SHEET

### Three Phase Induction Motor - Squirrel Cage



_	
Customer	
Custoffici	

#### Thermal protection

		•		
ID	Application	Туре	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			2/2	