## **DATA SHEET**

### Three Phase Induction Motor - Squirrel Cage



Customer Product line : W21 Explosion Proof High Efficiency Three-Product code: 11956039 : 586/7T Locked rotor time Frame : 126s (cold) 70s (hot) Output : 300 HP (220 kW) Temperature rise : 80 K Poles Duty cycle : Cont.(S1) : -20°C to +40°C Frequency : 60 Hz Ambient temperature : 460 V : 1000 m.a.s.l. Rated voltage Altitude Rated current : 355 A Protection degree : IP55 : IC411 - TEFC L. R. Amperes : 2166 A Cooling method **LRC** : 6.1x(Code G) Mounting : F-1 : Both (CW and CCW) No load current : 113 A Rotation<sup>1</sup> Rated speed : 1190 rpm Noise level<sup>2</sup> : 77.0 dB(A) Slip : 0.83 % Starting method : Direct On Line Rated torque : 1320 ft.lb Approx. weight<sup>3</sup> : 4253 lb Locked rotor torque : 180 % Breakdown torque : 200 % : F Insulation class Service factor : 1.15 Moment of inertia (J) : 277 sq.ft.lb Design 25% 50% 75% 100% Output Foundation loads Efficiency (%) 93.0 93.6 94.5 95.0 Max. traction : 3397 lb Power Factor 0.49 0.72 0.80 0.82 Max. compression : 7650 lb Non drive end Drive end Bearing type 6322 C3 6319 C3 00068 Viton Seal Sealing Lubrication interval 9212 h 11094 h Lubricant amount 60 g 45 g Lubricant type Mobil Polyrex EM

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			1/2	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



_	
Customer	
Custoffici	

#### Thermal protection

		•		
ID	Application	Туре	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary Performed		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			2/2	