

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA Premium
Efficiency Three-Phase

Product code : 11439680

Catalog # : 06036XT3E364TS

Frame : 364/5TS
Output : 60 HP (45 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 137/68.6 A
L. R. Amperes : 878/439 A
LRC : 6.4x(Code G)
No load current : 30.0/15.0 A
Rated speed : 3550 rpm
Slip : 1.39 %
Rated torque : 88.8 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 250 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 9.96 sq.ft.lb
Design : B

Locked rotor time : 108s (cold) 60s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 85.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 1065 lb

Output	50%	75%	100%
Efficiency (%)	92.4 92.0	93.0 92.8	93.6 93.0
	92.0 92.0	92.8 92.8	93.0 93.0
Power Factor	0.79 0.79	0.86 0.86	0.88 0.88
	0.77 0.76	0.85 0.85	0.88 0.87

Foundation loads
Max. traction : 358 lb
Max. compression : 1405 lb

	Drive end	Non drive end
Bearing type	: 6314 C3	6314 C3
Sealing	: Oil Seal	Lip Seal
Lubrication interval	: 3604 h	3604 h
Lubricant amount	: 27 g	27 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 2		
Checked by				
Date	28/03/2024			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date	28/03/2024				