DATA SHEET

Single Phase Induction Motor - Squirrel Cage



						· · · · · · · · · · · · · · · · · · ·	
Customer	:						
Product line	: Fan	and Exha	ust Single-F	Phase	Product code : Catalog # :	12205154 00182OS1AEC56	
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia	•	: 4 : 60 Hz : 115 V : 12.1 / : 52.0 / : 4.3x(0 : 10.6 / : 1725 : 4.17 ° : 3.06 f : 120 % : 240 % : B : 1.00	A A Code G) A rpm % t.lb		Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 10s (cold) 6s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP21 : IC01 - ODP : F-1 : CW : 46.0 dB(A) : Direct On Line : 27.8 lb	
Output	25%	50%	75%	100%	Foundation loads		
Efficiency (%) Power Factor			67.0 46.9 0.70 0.51		Max. traction Max. compression		
Bearing type Sealing Lubrication interva	al	:	Drive 6 6203 Without Be	3 ZZ	Non drive end 6201 ZZ Without Bearing Seal -		

Mobil Polyrex EM

Notes:

Lubricant amount Lubricant type

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer		

Thermal protection

ID	Application	Туре	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	130 °C

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			2/2	