

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Wash Down NEMA Premium Efficiency Three-Phase Product code : 15228368
Catalog # : 00736ET3EHW184T-S

Frame	: 182/4T	Locked rotor time	: 37s (cold) 21s (hot)
Output	: 7.5 HP (5.5 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 17.5/8.76 A	Protection degree	: IP56
L. R. Amperes	: 135/67.5 A	Cooling method	: IC411 - TEFC
LRC	: 7.7x(Code J)	Mounting	: F-1
No load current	: 6.07/3.04 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3475 rpm	Noise level ²	: 68.0 dB(A)
Slip	: 3.47 %	Starting method	: Direct On Line
Rated torque	: 11.3 ft.lb	Approx. weight ³	: 82.9 lb
Locked rotor torque	: 270 %		
Breakdown torque	: 360 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.1913 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	88.2	88.5	89.5	89.5	Max. traction	: 219 lb
Power Factor	0.49	0.74	0.83	0.88	Max. compression	: 302 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6206 2RS	6205 2RS
Sealing	:	Viton Oil seal with Stainless Steel Spring	Viton Oil seal with Stainless Steel Spring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:
USABLE @208V 19.0A SF 1.00 SFA 19.0A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 1		
Checked by				
Date	29/03/2024			