DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer Product line : W21 Explosion Proof NEMA Premium Product code: 14591686 Efficiency Three-Phase Catalog #: 00236XT3H145T Frame : 143/5T Locked rotor time : 27s (cold) 15s (hot) Output : 2 HP (1.5 kW) Temperature rise : 80 K Poles Duty cycle : Cont.(S1) : -20°C to +40°C Frequency : 60 Hz Ambient temperature Rated voltage : 575 V : 1000 m.a.s.l. Altitude Rated current : 2.15 A Protection degree : IP55 L. R. Amperes Cooling method : IC411 - TEFC : 19.8 A LRC : 9.2x(Code L) Mounting : F-1 No load current : 0.960 A Rotation¹ : Both (CW and CCW) Rated speed : 3495 rpm Noise level² : 68.0 dB(A) Starting method Slip : 2.92 % : Direct On Line Rated torque : 3.01 ft.lb Approx. weight³ : 71.6 lb Locked rotor torque : 370 % Breakdown torque : 420 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 0.0551 sq.ft.lb Design 25% 50% 75% 100% Output Foundation loads 80.0 84.0 85.5 : 73 lb Efficiency (%) 78.4 Max. traction Power Factor 0.41 0.64 0.76 0.82 : 146 lb Max. compression Drive end Non drive end Bearing type 6205 2RS 6204 2RS Sealing Oil Seal Lip Seal Lubrication interval Lubricant amount Lubricant type Mobil Polyrex EM

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



_	
Customer	
Custoffici	

Thermal protection

l		•		
ID	Application	Туре	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			2/2	