

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA Premium
Efficiency Three-Phase

Product code : 12408381

Catalog # : 20018XT3G504

Frame	: 504/5T	Locked rotor time	: 52s (cold) 29s (hot)
Output	: 200 HP (150 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 230 A	Protection degree	: IP55
L. R. Amperes	: 1564 A	Cooling method	: IC411 - TEFC
LRC	: 6.8x(Code G)	Mounting	: F-1
No load current	: 74.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1782 rpm	Noise level ²	: 82.0 dB(A)
Slip	: 1.00 %	Starting method	: Direct On Line
Rated torque	: 589 ft.lb	Approx. weight ³	: 2448 lb
Locked rotor torque	: 210 %		
Breakdown torque	: 229 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 76.2 sq.ft.lb		
Design	: A		

Output	25%		50%		75%		100%		Foundation loads	
Efficiency (%)	95.7	95.0	95.8	95.4	96.2	95.4	96.2	95.8	Max. traction	: 2713 lb
	95.3	95.3	95.4	95.4	95.8	95.8	95.8	95.8		
Power Factor	0.48	0.46	0.72	0.70	0.80	0.78	0.85	0.84	Max. compression	: 5161 lb
	0.42	0.38	0.65	0.61	0.75	0.73	0.82	0.81		

					<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:				6319 C3	6316 C3
Sealing	:				Viton Oil Seal	Viton Seal
Lubrication interval	:				7038 h	8569 h
Lubricant amount	:				45 g	34 g
Lubricant type	:				Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/03/2024			

Page 1 / 2
Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2Revision	
Checked by					
Date	28/03/2024				