DATA SHEET

Single Phase Induction Motor - Squirrel Cage



				•	•		
Customer	:						
Product line	: Fan	and Exhau	ust Single-l	Phase	Product code : Catalog # :	12215587 .5082OS1AEC56	
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia	е	: 4 : 60 Hz : 115 V : 8.20 A : 49.2 A : 6.0x(0 : 8.30 A : 1725 : 4.17 9 : 1.51 f : 130 % : 260 % : B	A A Code N) A rpm % t.lb	·)	Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Starting method Approx. weight³	: 10s (cold) 6s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP21 : IC01 - ODP : F-1 : CW : Direct On Line : 16.1 lb	
Output	25%	50%	75%	100%	Foundation loads		
Efficiency (%)	0.000 0.000		51.2 36.7		Max. traction		
Power Factor	0.00 0.00	0.45 0.45	0.55 0.52	0.64 0.59	Max. compression		
Bearing type Sealing Lubrication interva	al	: ,	<u>Drive</u> 6201 Without Be 0	I ZZ aring Seal	Non drive end 6201 ZZ Without Bearing Se 0 h	eal	
Lubricant amount		:	0	g	0 g		

Mobil Polyrex EM

Notes:

Lubricant type

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer		

Thermal protection

ID	Application	Туре	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	130 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			2/2	