## **DATA SHEET**

## Three Phase Induction Motor - Squirrel Cage



					9		
Customer	:						
Product line	: W22 Phase		Premium E	fficiency Th	ree- Product code :  Catalog # :	13500622 30012ET3GKD449T-W22	
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia (J) Design		: 6 : 60 F : 460 : 356 : 2747 : 7.7x : 170 : 1189 : 0.92 : 1320 : 270 : 300 : F : 1.00	HP (220 k Iz V A I A (Code J) A ) rpm % ) ft.lb %	W)	Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 18s (cold) 10s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 70.0 dB(A) : Direct On Line : 3113 lb	
		50%	75%	100%	Foundation loads		
		95.4 0.63	95.8 0.75	95.8 0.81	Max. traction Max. compression	: 9040 lb : 12154 lb	
Bearing type Sealing Lubrication interval Lubricant amount Lubricant type		:	NU- W 70	<u>e end</u> 322 C3 /Seal 000 h 60 g	Non drive end 6319 C3 WSeal 13000 h 45 g lobil Polyrex EM		

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary		Performed	Checked	Date	
Performed by							
Checked by					Page	Revision	
Date	27/03/2024				1/1		