## **DATA SHEET**

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Compressor Duty Standard Product code : 13571295

Efficiency Three-Phase

Catalog #: 00536OS3ECD56-S

Frame : 56H Locked rotor time : 9s (cold) 5s (hot)

Output : 5 HP (3.7 kW) Temperature rise : 105 K Poles : 2 Duty cycle : S3

Frequency : 60 Hz Ambient temperature : -20°C to +40°C Rated voltage : 208-230/460 V Altitude : 1000 m.a.s.l.

LRC : 5.5x(Code G) Rotation<sup>1</sup> : Both (CW and CCW)
No load current : 0.000-4.80/2.40 A Starting method : Direct On Line

Rated speed : 3390 rpm Approx. weight<sup>3</sup> : 33.4 lb

Rated torque : 7.75 ft.lb
Locked rotor torque : 170 %
Breakdown torque : 200 %
Insulation class : F
Service factor : 1.00

Moment of inertia (J) : 0.1092 sq.ft.lb

Design : A

25% 50% 75% 100% Output Foundation loads 0.000 81.0 79.0 : 135 lb Efficiency (%) 82.0 Max. traction : 169 lb Power Factor 0.00 0.88 0.92 0.79 Max. compression

Bearing type : 6204 ZZ 6202 ZZ
Sealing : Without Bearing Seal Without Bearing Seal

Lubrication interval:0 h0 hLubricant amount:0 g0 g

Lubricant type : Mobil Polyrex EM

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	26/03/2024			1/1	