

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel JM Pump NEMA Premium
Efficiency Three-Phase

Product code : 12676948

Catalog # : 00336OT3V145JM-S

Frame : 143/5JM
Output : 3 HP (2.2 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 200/400 V
Rated current : 8.26/4.13 A
L. R. Amperes : 66.1/33.0 A
LRC : 8.0x(Code J)
No load current : 2.99/1.49 A
Rated speed : 3480 rpm
Slip : 3.33 %
Rated torque : 4.53 ft.lb
Locked rotor torque : 229 %
Breakdown torque : 300 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.1279 sq.ft.lb
Design : B

Locked rotor time : 16s (cold) 9s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 62.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 42.2 lb

Output 25% 50% 75% 100%

Efficiency (%) 83.7 84.0 85.5 85.5
Power Factor 0.50 0.76 0.86 0.90

Foundation loads

Max. traction : 97 lb
Max. compression : 139 lb

	Drive end	Non drive end
Bearing type :	6206 ZZ	6203 ZZ
Sealing :	Without Bearing Seal	Without Bearing Seal
Lubrication interval :	-	-
Lubricant amount :	-	-
Lubricant type :	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 1		
Checked by				
Date	29/03/2024			