

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel JM Pump NEMA Premium
Efficiency Three-Phase

Product code : 13419558

Catalog # : 00736ET3E184JM-S

Frame : 182/4JM
Output : 7.5 HP (5.5 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 17.5/8.76 A
L. R. Amperes : 135/67.5 A
LRC : 7.7x(Code J)
No load current : 6.07/3.04 A
Rated speed : 3475 rpm
Slip : 3.47 %
Rated torque : 11.3 ft.lb
Locked rotor torque : 270 %
Breakdown torque : 360 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.1913 sq.ft.lb
Design : B

Locked rotor time : 37s (cold) 21s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 68.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 90.1 lb

Output	25%	50%	75%	100%
Efficiency (%)	88.2	88.5	89.5	89.5
Power Factor	0.49	0.74	0.83	0.88

Foundation loads
Max. traction : 216 lb
Max. compression : 306 lb

	Drive end	Non drive end
Bearing type	6207 ZZ	6205 ZZ
Sealing	V'Ring	V'Ring
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	Mobil Polyrex EM	

Notes:
USABLE @208V 19.0A SF 1.00 SFA 19.0A

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 1		
Checked by				
Date	29/03/2024			