## **DATA SHEET**

## Three Phase Induction Motor - Squirrel Cage



Customer	:					
Product line		e Coupled ency Three		MA Premiu	m Product code :  Catalog # :	13468371 03036OT3E284JPV
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia Design	•	: 2 : 60 Hz : 230/4 : 70.0/3 : 441/2	2 (22 kW) 60 V 65.0 A 21 A Code G) 2.9 A rpm 6		Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 18s (cold) 10s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP23 : IC01 - ODP : W-6 : Both (CW and CCW) : 72.0 dB(A) : Direct On Line : 344 lb
Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	88.2 88.3 91.8 89.8 91.1	89.8 89.8 90.8 90.0 91.0	91.7 90.7 90.8 90.8 90.8 90.2 91.0	92.4 92.4 89.5 90.2 90.7	Max. traction	: 341 lb
Power Factor	0.45 0.42	0.70 0.66	0.82 0.83 0.80 0.77 0.86 0.83 0.81	0.85 0.83	Max. compression	: 685 lb
Bearing type Sealing Lubrication interva Lubricant amount Lubricant type  Notes:	al	: \	<u>Drive 6</u> 6311 2 Without Be 1151 18	Z C3 aring Seal 7 h g	Non drive end 6211 Z C3 Without Bearing Se 14226 h 11 g bil Polyrex EM	al

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/1	