

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel JM Pump High Efficiency Three-Phase Product code : 12951404

Frame	: 213/5JM	Locked rotor time	: 10s (cold) 6s (hot)
Output	: 15 HP (11 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 200/400 V	Altitude	: 1000 m.a.s.l.
Rated current	: 40.2/20.1 A	Cooling method	: IC01 - ODP
L. R. Amperes	: 262/131 A	Mounting	: F-1
LRC	: 6.5x(Code G)	Rotation ¹	: Both (CW and CCW)
No load current	: 16.9/8.46 A	Noise level ²	: 66.0 dB(A)
Rated speed	: 3525 rpm	Starting method	: Direct On Line
Slip	: 2.08 %	Approx. weight ³	: 126 lb
Rated torque	: 22.3 ft.lb		
Locked rotor torque	: 190 %		
Breakdown torque	: 260 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.4651 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	88.3	88.5	89.5	89.5	Max. traction	: 265 lb
Power Factor	0.46	0.73	0.83	0.88	Max. compression	: 390 lb

	Drive end	Non drive end
Bearing type	: 6209 ZZ	: 6206 ZZ
Sealing	: Without Bearing Seal	: Without Bearing Seal
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 1		
Checked by				
Date	29/03/2024			