

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel JM Pump High Efficiency Three-Phase Product code : 12682536

Frame	: 143/5JM	Locked rotor time	: 21s (cold) 12s (hot)
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 2.95 A	Cooling method	: IC01 - ODP
L. R. Amperes	: 23.0 A	Mounting	: F-1
LRC	: 7.8x(Code J)	Rotation ¹	: Both (CW and CCW)
No load current	: 1.28 A	Noise level ²	: 62.0 dB(A)
Rated speed	: 3475 rpm	Starting method	: Direct On Line
Slip	: 3.47 %	Approx. weight ³	: 38.7 lb
Rated torque	: 4.53 ft.lb		
Locked rotor torque	: 250 %		
Breakdown torque	: 310 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0496 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	83.8	84.0	84.0	84.0	Max. traction	: 103 lb
Power Factor	0.45	0.73	0.84	0.89	Max. compression	: 141 lb

	Drive end	Non drive end
Bearing type	: 6206 ZZ	: 6203 ZZ
Sealing	: Without Bearing Seal	: Without Bearing Seal
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1 Revision		
Checked by				
Date	29/03/2024			