## **DATA SHEET**

## Three Phase Induction Motor - Squirrel Cage



Customer	:					
Product line : Close Coupled Pump NEMA Premium Efficiency Three-Phase					m Product code : Catalog # :	13469140 06036OT3E326JPV
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia Design	(J)	: 326JP : 60 HP : 2 : 60 Hz : 230/46 : 142/71 : 852/42 : 6.0x(Co : 43.0/21 : 3560 rp : 1.11 % : 88.5 ft. : 220 % : 229 % : F : 1.15 : 4.36 so : B	0 V .0 A 6 A ode G) 1.5 A om		Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 43s (cold) 24s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP23 : IC01 - ODP : W-6 : Both (CW and CCW) : 75.0 dB(A) : Direct On Line : 537 lb
Output			75%	100%	Foundation loads	
Efficiency (%) Power Factor	0.53 0.54 0.7 0.49 0.46 0.7 0.59 0.54 0.8	9.9 91.0 9.2 91.0 1.7 77 0.77 73 0.70 80 0.77	91.5 93.0 91.0 91.7 92.4 0.84 0.83 0.81 0.79	93.7 93.8 91.7 92.9 93.0 0.85 0.86 0.84 0.83	Max. traction  Max. compression	: 590 lb : 1128 lb
Bearing type Sealing Lubrication interva Lubricant amount Lubricant type Notes:		W	Drive 6 6312 2 Vithout Be 9829 21	Z C3 aring Seal 9 h g	Non drive end 6212 Z C3 Without Bearing S 12143 h 13 g bil Polyrex EM	eal

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

` '					
Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	29/03/2024	1		1 / 1	