

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Close Coupled Pump NEMA Premium
Efficiency Three-Phase

Product code : 11266733

Catalog # : 06018OT3G364JM

Frame : 364/5JM
Output : 60 HP (45 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 460 V
Rated current : 69.9 A
L. R. Amperes : 468 A
LRC : 6.7x(Code G)
No load current : 22.0 A
Rated speed : 1780 rpm
Slip : 1.11 %
Rated torque : 177 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 250 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 15.6 sq.ft.lb
Design : B

Locked rotor time : 27s (cold) 15s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP23
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 68.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 799 lb

Output	25%	50%	75%	100%				
Efficiency (%)	94.0	93.9	94.5	94.5	94.5	94.5	95.0	95.0
Power Factor	0.50	0.57	0.74	0.79	0.83	0.87	0.85	0.89
	0.52	0.48	0.75	0.72	0.84	0.82	0.87	0.86

Foundation loads
Max. traction : 1352 lb
Max. compression : 2150 lb

	Drive end	Non drive end
Bearing type	: 6314 C3	: 6314 C3
Sealing	: Without Bearing Seal	: Without Bearing Seal
Lubrication interval	: 20000 h	: 20000 h
Lubricant amount	: 27 g	: 27 g
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	29/03/2024			
		Revision		