

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel JM Pump High Efficiency Three-Phase Product code : 12963815

| | | | |
|-----------------------|-------------------|-----------------------------|-----------------------|
| Frame | : 254/6JM | Locked rotor time | : 16s (cold) 9s (hot) |
| Output | : 20 HP (15 kW) | Temperature rise | : 80 K |
| Poles | : 2 | Duty cycle | : Cont.(S1) |
| Frequency | : 60 Hz | Ambient temperature | : -20°C to +40°C |
| Rated voltage | : 200/400 V | Altitude | : 1000 m.a.s.l. |
| Rated current | : 54.5/27.3 A | Cooling method | : IC01 - ODP |
| L. R. Amperes | : 327/164 A | Mounting | : W-6 |
| LRC | : 6.0x(Code G) | Rotation ¹ | : Both (CW and CCW) |
| No load current | : 21.0/10.5 A | Noise level ² | : 70.0 dB(A) |
| Rated speed | : 3520 rpm | Starting method | : Direct On Line |
| Slip | : 2.22 % | Approx. weight ³ | : 176 lb |
| Rated torque | : 29.8 ft.lb | | |
| Locked rotor torque | : 180 % | | |
| Breakdown torque | : 240 % | | |
| Insulation class | : F | | |
| Service factor | : 1.15 | | |
| Moment of inertia (J) | : 0.6974 sq.ft.lb | | |
| Design | : B | | |

| | | | | | | |
|----------------|------|------|------|------|------------------|----------|
| Output | 25% | 50% | 75% | 100% | Foundation loads | |
| Efficiency (%) | 87.7 | 88.5 | 89.5 | 90.2 | Max. traction | : 255 lb |
| Power Factor | 0.48 | 0.75 | 0.84 | 0.88 | Max. compression | : 431 lb |

| | Drive end | Non drive end |
|----------------------|------------------------|----------------------|
| Bearing type | : 6309 Z C3 | 6208 Z C3 |
| Sealing | : Without Bearing Seal | Without Bearing Seal |
| Lubrication interval | : 15797 h | 20000 h |
| Lubricant amount | : 13 g | 8 g |
| Lubricant type | Mobil Polyrex EM | |

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev. | Changes Summary | Performed | Checked | Date |
|--------------|-----------------|-----------|---------|------|
| | | | | |
| Performed by | | | | |
| Checked by | | | | |
| Date | 29/03/2024 | | | |

Page 1 / 1
Revision