

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel JP Pump High Efficiency Three-Phase Product code : 12734495

Frame	: 254/6JP	Locked rotor time	: 16s (cold) 9s (hot)
Output	: 20 HP (15 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 19.0 A	Cooling method	: IC01 - ODP
L. R. Amperes	: 114 A	Mounting	: W-6
LRC	: 6.0x(Code G)	Rotation ¹	: Both (CW and CCW)
No load current	: 7.30 A	Noise level ²	: 70.0 dB(A)
Rated speed	: 3520 rpm	Starting method	: Direct On Line
Slip	: 2.22 %	Approx. weight ³	: 178 lb
Rated torque	: 29.8 ft.lb		
Locked rotor torque	: 180 %		
Breakdown torque	: 240 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.6974 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	87.7	88.5	89.5	90.2	Max. traction	: 254 lb
Power Factor	0.48	0.75	0.84	0.88	Max. compression	: 432 lb

	Drive end	Non drive end
Bearing type	: 6309 Z C3	6208 Z C3
Sealing	: Without Bearing Seal	Without Bearing Seal
Lubrication interval	: 15797 h	20000 h
Lubricant amount	: 13 g	8 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/03/2024			

Page 1 / 1
Revision