

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM High Efficiency Three-Phase

Product code : 12423175

| | | | |
|-----------------------|-----------------|-----------------------------|------------------------|
| Frame | : 254/6JM | Locked rotor time | : 18s (cold) 10s (hot) |
| Output | : 20 HP (15 kW) | Temperature rise | : 80 K |
| Poles | : 2 | Duty cycle | : Cont.(S1) |
| Frequency | : 60 Hz | Ambient temperature | : -20°C to +40°C |
| Rated voltage | : 575 V | Altitude | : 1000 m.a.s.l. |
| Rated current | : 19.0 A | Protection degree | : IP55 |
| L. R. Amperes | : 114 A | Cooling method | : IC411 - TEFC |
| LRC | : 6.0x(Code G) | Mounting | : F-1 |
| No load current | : 4.56 A | Rotation ¹ | : Both (CW and CCW) |
| Rated speed | : 3515 rpm | Noise level ² | : 72.0 dB(A) |
| Slip | : 2.36 % | Starting method | : Direct On Line |
| Rated torque | : 29.9 ft.lb | Approx. weight ³ | : 280 lb |
| Locked rotor torque | : 200 % | | |
| Breakdown torque | : 250 % | | |
| Insulation class | : F | | |
| Service factor | : 1.25 | | |
| Moment of inertia (J) | : 1.54 sq.ft.lb | | |
| Design | : B | | |

| | | | | | | |
|----------------|------|------|------|------|------------------|----------|
| Output | 25% | 50% | 75% | 100% | Foundation loads | |
| Efficiency (%) | 90.0 | 90.2 | 90.2 | 90.2 | Max. traction | : 218 lb |
| Power Factor | 0.56 | 0.78 | 0.85 | 0.88 | Max. compression | : 498 lb |

| | | | |
|----------------------|---|------------------|----------------------|
| | | <u>Drive end</u> | <u>Non drive end</u> |
| Bearing type | : | 6309 C3 | 6209 C3 |
| Sealing | : | V'Ring | V'Ring |
| Lubrication interval | : | 19000 h | 20000 h |
| Lubricant amount | : | 13 g | 9 g |
| Lubricant type | : | Mobil Polyrex EM | |

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev. | Changes Summary | Performed | Checked | Date |
|--------------|-----------------|---------------|----------|------|
| | | | | |
| Performed by | | Page 1 / 1 | | |
| Checked by | | | | |
| Date | 29/03/2024 | | | |
| | | | Revision | |