

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JP NEMA  
Premium Efficiency Three-Phase

Product code : 12711612

Catalog # : 00536ET3H184JP-W22

Frame : 182/4JP  
Output : 5 HP (3.7 kW)  
Poles : 2  
Frequency : 60 Hz  
Rated voltage : 575 V  
Rated current : 4.72 A  
L. R. Amperes : 35.9 A  
LRC : 7.6x(Code J)  
No load current : 1.60 A  
Rated speed : 3500 rpm  
Slip : 2.78 %  
Rated torque : 7.50 ft.lb  
Locked rotor torque : 229 %  
Breakdown torque : 350 %  
Insulation class : F  
Service factor : 1.25  
Moment of inertia (J) : 0.2233 sq.ft.lb  
Design : B

Locked rotor time : 32s (cold) 18s (hot)  
Temperature rise : 80 K  
Duty cycle : Cont.(S1)  
Ambient temperature : -20°C to +40°C  
Altitude : 1000 m.a.s.l.  
Protection degree : IP55  
Cooling method : IC411 - TEFC  
Mounting : F-1  
Rotation<sup>1</sup> : Both (CW and CCW)  
Noise level<sup>2</sup> : 66.0 dB(A)  
Starting method : Direct On Line  
Approx. weight<sup>3</sup> : 100 lb

Output 25% 50% 75% 100%

Efficiency (%) 86.1 86.5 88.5 88.5  
Power Factor 0.51 0.76 0.85 0.89

Foundation loads

Max. traction : 117 lb  
Max. compression : 218 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
12.2	10.1	9.7	5.9	3.7	2.3	1.5

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type :		6307 ZZ	6206 ZZ
Sealing :		V'Ring	V'Ring
Lubrication interval :		-	-
Lubricant amount :		-	-
Lubricant type :		Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	30/03/2024			
			Page 1 / 1	Revision