

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel JP Pump NEMA Premium
Efficiency Three-Phase

Product code : 14808413

Catalog # : 00156ET3E143JP-S

Frame : 143/5JP
Output : 1.5 HP (1.1 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 3.74/1.87 A
L. R. Amperes : 34.0/17.0 A
LRC : 9.1x(Code L)
No load current : 1.72/0.859 A
Rated speed : 3520 rpm
Slip : 2.22 %
Rated torque : 2.24 ft.lb
Locked rotor torque : 229 %
Breakdown torque : 300 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.1023 sq.ft.lb
Design : B

Locked rotor time : 30s (cold) 17s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 68.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 2.2 lb

Output	25%		50%		75%		100%	
Efficiency (%)	78.4	83.1	80.0	82.6	82.5	83.8	84.0	82.9
	81.4		81.7		84.0		83.9	
Power Factor	0.44	0.49	0.71	0.77	0.82	0.87	0.88	0.91
	0.43		0.70		0.82		0.88	

Foundation loads
Max. traction : 76 lb
Max. compression : 78 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6206 ZZ	6203 ZZ
Sealing	:	V'Ring	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	29/03/2024			
			Revision	