DATA SHEET

Three Phase Induction Motor - Squirrel Cage



				•	3				
Customer	:								
Product line	: ODP Phase		remium Effi	iciency Thre	ee- Product code : Catalog # :	12440442 02036OT3ECD254TF2			
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia Design	•	: 2 : 60 Hz : 230/4 : 49.2/2 : 276/1 : 5.6x(0 : 18.2/9 : 2.22 % : 29.8 f : 160 % : 250 %	60 V 24.6 A 38 A Code F) 0.10 A rpm % t.lb		Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 21s (cold) 12s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP23 : IC01 - ODP : F-2 : Both (CW and CCW) : 66.0 dB(A) : Direct On Line : 209 lb			
Output	25%	50%	75%	100%	Foundation loads				
Efficiency (%) Power Factor	0.46 0.43	84.4 85.0 86.5 86.5 87.5 0.71 0.65	86.9 87.9 87.5 87.5 88.5 0.80 0.77	91.2 91.4 87.5 87.5 88.5 0.84 0.83	Max. traction Max. compression	: 309 lb : 518 lb			
	0.39 0.34 (0.51 0.46 (0.41								
Bearing type Sealing Lubrication interva Lubricant amount Lubricant type		: : '	Drive 6 6309 Without Be 2000 13	Z C3 aring Seal 00 h g	Non drive end 6209 Z C3 Without Bearing Sea 20000 h 9 g bil Polyrex EM	6209 Z C3 Without Bearing Seal 20000 h 9 g			
Notes:									

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed		Checked	Date
Performed by						
Checked by					Page	Revision
Date	26/03/2024				1/1	