

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel JP Pump High Efficiency
Three-Phase

Product code : 13550936

Catalog # : 02036OP3VFP254JPV-S

Frame : 254/6JP
Output : 20 HP (15 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 200/400 V
Rated current : 54.5/27.3 A
L. R. Amperes : 327/164 A
LRC : 6.0x(Code G)
No load current : 21.0/10.5 A
Rated speed : 3520 rpm
Slip : 2.22 %
Rated torque : 29.8 ft.lb
Locked rotor torque : 180 %
Breakdown torque : 240 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.6974 sq.ft.lb
Design : B

Locked rotor time : 16s (cold) 9s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Cooling method : IC01 - ODP
Mounting : W-6
Rotation¹ : Both (CW and CCW)
Noise level² : 70.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 169 lb

Output	25%	50%	75%	100%
--------	-----	-----	-----	------

Efficiency (%)	87.7	88.5	89.5	90.2
Power Factor	0.48	0.75	0.84	0.88

Foundation loads

Max. traction : 259 lb
Max. compression : 428 lb

	Drive end	Non drive end
Bearing type	6309 Z C3	6208 Z C3
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	15797 h	20000 h
Lubricant amount	13 g	8 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	26/03/2024			
		Revision		