

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Close Coupled Pump High Efficiency Three-Phase
Product code : 10596920
Catalog # : 04036OP3E286JMV

Frame	: 286JM	Locked rotor time	: 48s (cold) 27s (hot)
Output	: 40 HP (30 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 93.4/46.7 A	Protection degree	: IP23
L. R. Amperes	: 579/290 A	Cooling method	: IC01 - ODP
LRC	: 6.2x(Code G)	Mounting	: W-6
No load current	: 26.0/13.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3545 rpm	Noise level ²	: 73.0 dB(A)
Slip	: 1.53 %	Starting method	: Direct On Line
Rated torque	: 59.3 ft.lb	Approx. weight ³	: 373 lb
Locked rotor torque	: 229 %		
Breakdown torque	: 210 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 2.16 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads				
Efficiency (%)	91.6	89.9	91.7	89.5	91.7	90.2	91.7	89.5	Max. traction : 437 lb
	89.9	89.3	89.5	89.5	90.2	90.2	89.5	90.2	
Power Factor	0.55	0.63	0.79	0.84	0.86	0.88	0.88	0.89	Max. compression : 810 lb
	0.57	0.53	0.81	0.78	0.86	0.85	0.88	0.87	

				<u>Drive end</u>		<u>Non drive end</u>
Bearing type	:			6311 Z C3		6211 Z C3
Sealing	:			Without Bearing Seal		Without Bearing Seal
Lubrication interval	:			11517 h		14226 h
Lubricant amount	:			18 g		11 g
Lubricant type	:			Mobil Polyrex EM		

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/03/2024			
			Page	Revision
			1 / 1	