

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Close Coupled Pump High Efficiency Three-Phase Product code : 11518744

Frame	: 364/5JP	Locked rotor time	: 27s (cold) 15s (hot)
Output	: 75 HP (55 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 200/400 V	Altitude	: 1000 m.a.s.l.
Rated current	: 194/96.9 A	Protection degree	: IP23
L. R. Amperes	: 1222/611 A	Cooling method	: IC01 - ODP
LRC	: 6.3x(Code G)	Mounting	: W-6
No load current	: 64.4/32.2 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3555 rpm	Noise level ²	: 80.0 dB(A)
Slip	: 1.25 %	Starting method	: Direct On Line
Rated torque	: 111 ft.lb	Approx. weight ³	: 759 lb
Locked rotor torque	: 180 %		
Breakdown torque	: 270 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 6.81 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	92.3	92.4	93.0	93.0	Max. traction	: 645 lb
Power Factor	0.53	0.80	0.86	0.88	Max. compression	: 1404 lb

	Drive end	Non drive end
Bearing type	: 6314 C3	: 6314 C3
Sealing	: Without Bearing Seal	: Without Bearing Seal
Lubrication interval	: 7209 h	: 7209 h
Lubricant amount	: 27 g	: 27 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1 Revision		
Checked by				
Date	28/03/2024			