

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 JM Pump NEMA Premium Efficiency
Three-Phase

Product code : 14269583

Catalog # : 07518OT3H365JM-W40

Frame : 364/5JM
Output : 75 HP (55 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 575 V
Rated current : 68.4 A
L. R. Amperes : 465 A
LRC : 6.8x(Code G)
No load current : 24.4 A
Rated speed : 1780 rpm
Slip : 1.11 %
Rated torque : 221 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 260 %
Insulation class : F
Service factor : 1.25
Moment of inertia (J) : 16.8 sq.ft.lb
Design : B

Locked rotor time : 25s (cold) 14s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP23
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 69.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 811 lb

Output 25% 50% 75% 100%

Efficiency (%) 94.4 94.5 95.0 95.0
Power Factor 0.48 0.73 0.82 0.85

Foundation loads

Max. traction : 1566 lb
Max. compression : 2377 lb

	Drive end	Non drive end
Bearing type :	6314 C3	6212 Z C3
Sealing :	Without Bearing Seal	Without Bearing Seal
Lubrication interval :	20000 h	20000 h
Lubricant amount :	27 g	13 g
Lubricant type :	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 1		
Checked by				
Date	30/03/2024			