

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 High Efficiency Three-Phase

Product code :

15100491

Catalog # :

06018OP3EFP326TS-W40

Frame : 324/6TS
Output : 60 HP (45 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 208-230/460 V
Rated current : 159-144/71.8 A
L. R. Amperes : 954-864/431 A
LRC : 6.0x(Code G)
No load current : 46.5-51.4/25.7 A
Rated speed : 1770 rpm
Slip : 1.67 %
Rated torque : 178 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 220 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 7.08 sq.ft.lb
Design : B

Locked rotor time : 21s (cold) 12s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP23
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 66.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 509 lb

Output	25%	50%	75%	100%
Efficiency (%)	0.000	93.0	93.6	93.6
Power Factor	0.00	0.71	0.80	0.84

Foundation loads
Max. traction
Max. compression

	Drive end	Non drive end
Bearing type	6312 Z C3	6211 Z C3
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	4500 h	4500 h
Lubricant amount	21 g	11 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	26/03/2024			
		Revision		