

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Close Coupled Pump NEMA Premium
Efficiency Three-Phase

Product code : 13469635

Catalog # : 02036OT3V254JM

Frame : 254JM
Output : 20 HP (15 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 200/400 V
Rated current : 56.6/28.3 A
L. R. Amperes : 317/158 A
LRC : 5.6x(Code F)
No load current : 20.9/10.5 A
Rated speed : 3520 rpm
Slip : 2.22 %
Rated torque : 29.8 ft.lb
Locked rotor torque : 160 %
Breakdown torque : 250 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.7328 sq.ft.lb
Design : B

Locked rotor time : 21s (cold) 12s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP23
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 66.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 200 lb

Output	25%	50%	75%	100%
--------	-----	-----	-----	------

Efficiency (%)	88.6	89.5	90.2	91.0
Power Factor	0.46	0.71	0.80	0.84

Foundation loads

Max. traction : 257 lb
Max. compression : 458 lb

	Drive end	Non drive end
Bearing type	6309 Z C3	6209 Z C3
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	20000 h	20000 h
Lubricant amount	13 g	9 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	28/03/2024			
		Revision		