

Three Phase Induction Motor - Squirrel Cage



Product line : Multimounting High Efficiency Three-Phase Product code : 14324210
Catalog # : .2509EP3WAL80-W22

Output	25%	50%	75%	100%	Foundation loads					
Efficiency (%)	49.6	54.7	52.0	56.5	61.0	62.5	63.8	64.2	Max. traction	: 26 lb
	44.7		47.2		54.3		57.5			
Power Factor	0.25	0.22	0.43	0.40	0.55	0.52	0.63	0.59	Max. compression	: 53 lb
	0.24		0.43		0.54		0.63			

	<u>Drive end</u>	<u>Non drive end</u>
Bearing type :	6204 ZZ	6203 ZZ
Sealing :	Oil Seal	Oil Seal
Lubrication interval :	-	-
Lubricant amount :	-	-
Lubricant type :	Mobil Polyrex EM	

<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>	<p>These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.</p>
---	---

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				1 / 1	
Date	26/03/2024				