

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM High Efficiency Three-Phase

Product code : 11524340

Frame	: 324/6JM	Locked rotor time	: 30s (cold) 17s (hot)
Output	: 60 HP (45 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 140/69.8 A	Protection degree	: IP55
L. R. Amperes	: 838/419 A	Cooling method	: IC411 - TEFC
LRC	: 6.0x(Code F)	Mounting	: F-1
No load current	: 37.0/18.5 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3550 rpm	Noise level ²	: 76.0 dB(A)
Slip	: 1.39 %	Starting method	: Direct On Line
Rated torque	: 88.8 ft.lb	Approx. weight ³	: 588 lb
Locked rotor torque	: 229 %		
Breakdown torque	: 240 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 5.32 sq.ft.lb		
Design	: B		

Output	25%		50%		75%		100%		Foundation loads	
Efficiency (%)	92.2	92.8	92.4	92.4	93.0	93.0	93.0	92.4	Max. traction	: 659 lb
	92.2	92.2	92.4	92.4	93.0	93.0	93.0	93.0		
Power Factor	0.57	0.58	0.80	0.81	0.86	0.86	0.87	0.88	Max. compression	: 1247 lb
	0.54	0.51	0.78	0.76	0.85	0.83	0.87	0.86		

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	7.1	7.7	7.1	7.1
	P2 (0,5;1,0)	5.4	5.9	5.4	5.4
	P3 (0,25;1,0)	5.1	5.5	5.1	5.1
	P4 (0,9;0,5)	3.5	3.9	3.5	3.5
	P5 (0,5;0,5)	2.1	2.3	2.1	2.1
	P6 (0,5;0,25)	1.3	1.4	1.3	1.3
	P7 (0,25;0,25)	0.8	0.8	0.8	0.8

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6312 C3	6212 C3
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	12000 h	15000 h
Lubricant amount	:	21 g	13 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	29/03/2024			
			Revision	