

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IE2 Three-Phase

Product code :

14420816

Catalog # :

E03736EP3Y200LF3-W22

Frame : 200L  
Output : 37 kW (50 HP)  
Poles : 2  
Frequency : 50 Hz  
Rated voltage : 380/660 V  
Rated current : 69.5/40.0 A  
L. R. Amperes : 528/304 A  
LRC : 7.6  
No load current : 24.0/13.8 A  
Rated speed : 2965 rpm  
Slip : 1.17 %  
Rated torque : 87.9 ft.lb  
Locked rotor torque : 290 %  
Breakdown torque : 280 %  
Insulation class : F  
Service factor : 1.00  
Moment of inertia (J) : 4.63 sq.ft.lb  
Design : N

Locked rotor time : 21s (cold) 12s (hot)  
Temperature rise : 80 K  
Duty cycle : S1  
Ambient temperature : -20°C to +40°C  
Altitude : 1000 m.a.s.l.  
Protection degree : IP55  
Cooling method : IC411 - TEFC  
Mounting : B3T  
Rotation<sup>1</sup> : Both (CW and CCW)  
Noise level<sup>2</sup> : 72.0 dB(A)  
Starting method : Direct On Line  
Approx. weight<sup>3</sup> : 595 lb

Output	25%		50%		75%		100%	
Efficiency (%)	91.8	91.9	92.0	92.3	93.0	93.0	93.0	93.3
	91.7	90.7	92.0	91.1	93.4	92.7	93.5	93.0
Power Factor	0.50	0.45	0.76	0.70	0.84	0.80	0.87	0.85
	0.39	0.40	0.63	0.60	0.76	0.78	0.82	0.83

Foundation loads  
Max. traction : 736 lb  
Max. compression : 1332 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	7.1	6.8	6.6	7.1
	P2 (0,5;1,0)	5.7	5.5	5.3	5.7
	P3 (0,25;1,0)	5.5	5.2	5.0	5.5
	P4 (0,9;0,5)	3.8	3.6	3.5	3.8
	P5 (0,5;0,5)	2.4	2.3	2.2	2.4
	P6 (0,5;0,25)	1.6	1.6	1.5	1.6
	P7 (0,25;0,25)	1.1	1.0	1.0	1.1

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6312 ZZ C3	6212 ZZ C3
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2		
Checked by				
Date	26/03/2024			
		Revision		

Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date	26/03/2024				