

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IE2 Three-Phase

Product code : 14420282
Catalog # : E03012EP3Y225SMF3-W2

Frame	: 225S/M	Locked rotor time	: 21s (cold) 12s (hot)
Output	: 30 kW (40 HP)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 380/660 V	Altitude	: 1000 m.a.s.l.
Rated current	: 59.2/34.1 A	Protection degree	: IP55
L. R. Amperes	: 367/211 A	Cooling method	: IC411 - TEFC
LRC	: 6.2	Mounting	: B3T
No load current	: 24.0/13.8 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 985 rpm	Noise level ²	: 63.0 dB(A)
Slip	: 1.50 %	Starting method	: Direct On Line
Rated torque	: 215 ft.lb	Approx. weight ³	: 792 lb
Locked rotor torque	: 220 %		
Breakdown torque	: 250 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 17.1 sq.ft.lb		
Design	: N		

Output	25%		50%		75%		100%		Foundation loads	
Efficiency (%)	91.6	91.6	91.7	91.7	91.7	91.7	91.7	91.7	Max. traction	: 1553 lb
	91.2	91.0	91.3	91.7	91.7	92.4	91.7	93.0		
Power Factor	0.44	0.39	0.70	0.65	0.79	0.76	0.84	0.82	Max. compression	: 2346 lb
	0.36	0.39	0.62	0.66	0.73	0.76	0.80	0.81		

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	8.7	8.7	8.7	7.3
	P2 (0,5;1,0)	7.3	7.3	7.3	6.0
	P3 (0,25;1,0)	6.6	6.6	6.6	5.5
	P4 (0,9;0,5)	4.1	4.1	4.1	3.4
	P5 (0,5;0,5)	2.8	2.8	2.8	2.3
	P6 (0,5;0,25)	1.8	1.8	1.8	1.5
	P7 (0,25;0,25)	1.3	1.3	1.3	1.0

		Drive end	Non drive end
Bearing type	:	6314 C3	6314 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	20000 h	20000 h
Lubricant amount	:	27 g	27 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	26/03/2024			
			Page	Revision
			1 / 2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date	26/03/2024				