

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IE2 Three-Phase

Product code : 14414749  
Catalog # : E00712EP3Y160MF3-W22

Frame	: 160M	Locked rotor time	: 30s (cold) 17s (hot)
Output	: 7.5 kW (10 HP)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 380/660 V	Altitude	: 1000 m.a.s.l.
Rated current	: 15.9/9.15 A	Protection degree	: IP55
L. R. Amperes	: 92.2/53.1 A	Cooling method	: IC411 - TEFC
LRC	: 5.8	Mounting	: B3T
No load current	: 7.30/4.20 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 970 rpm	Noise level <sup>2</sup>	: 57.0 dB(A)
Slip	: 3.00 %	Starting method	: Direct On Line
Rated torque	: 54.5 ft.lb	Approx. weight <sup>3</sup>	: 249 lb
Locked rotor torque	: 210 %		
Breakdown torque	: 240 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 2.92 sq.ft.lb		
Design	: N		

Output	25%	50%	75%	100%	Foundation loads				
Efficiency (%)	86.8	86.7	87.0	86.9	87.2	87.2	87.2	Max. traction : 584 lb	
	85.7	86.7	86.0	87.0	87.2	89.5	87.2		89.5
Power Factor	0.41	0.36	0.67	0.62	0.77	0.73	0.82	0.80	Max. compression : 833 lb
	0.33	0.34	0.59	0.59	0.71	0.71	0.78	0.78	

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	14.6	14.6	14.6	11.7
	P2 (0,5;1,0)	13.3	13.3	13.3	10.6
	P3 (0,25;1,0)	12.3	12.3	12.3	9.8
	P4 (0,9;0,5)	6.9	6.9	6.9	5.5
	P5 (0,5;0,5)	5.0	5.0	5.0	4.0
	P6 (0,5;0,25)	3.3	3.3	3.3	2.7
	P7 (0,25;0,25)	2.4	2.4	2.4	1.9

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6309 ZZ C3	6209 ZZ C3
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	26/03/2024			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2Revision	
Checked by					
Date	26/03/2024				