

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Tru-Metric IE3 Three-Phase

Product code : 11701286
Catalog # : 00436ET3Y112M-W22

Frame	: 112M	Locked rotor time	: 25s (cold) 14s (hot)
Output	: 5.5 HP (4 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 380 V	Altitude	: 1000 m.a.s.l.
Rated current	: 7.83 A	Protection degree	: IP55
L. R. Amperes	: 60.3 A	Cooling method	: IC411 - TEFC
LRC	: 7.7	Mounting	: B3L(E)
No load current	: 2.80 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 2890 rpm	Noise level ²	: 64.0 dB(A)
Slip	: 3.67 %	Starting method	: Direct On Line
Rated torque	: 10.0 ft.lb	Approx. weight ³	: 93.8 lb
Locked rotor torque	: 229 %		
Breakdown torque	: 310 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.1898 sq.ft.lb		
Design	: N		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	88.0 87.5	88.2 88.0	88.2 88.4	Max. traction	: 185 lb
	85.5	87.5	88.5		
Power Factor	0.73 0.65	0.83 0.77	0.88 0.84	Max. compression	: 278 lb
	0.67	0.79	0.85		

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	12.6	12.4	12.3
	P2 (0,5;1,0)	9.9	9.7	9.6
	P3 (0,25;1,0)	9.6	9.5	9.4
	P4 (0,9;0,5)	7.3	7.1	7.0
	P5 (0,5;0,5)	4.5	4.4	4.4
	P6 (0,5;0,25)	3.3	3.2	3.2
	P7 (0,25;0,25)	2.2	2.1	2.1

		Drive end	Non drive end
Bearing type	:	6207 ZZ	6206 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	26/03/2024			
		Page		Revision
		1 / 1		