DATA SHEET

Three Phase Induction Motor - Squirrel Cage



				•	•		
Customer		:					
Product line : Rolled Steel JM Pump NEMA Premi Efficiency Three-Phase					ium Product code : Catalog # :	13312539 01036ET3H215JM-S	
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia (J) Design		: 213/5JM : 10 HP (7.5 kW) : 2 : 60 Hz : 575 V : 9.20 A : 69.0 A : 7.5x(Code H) : 3.01 A : 3530 rpm : 1.94 % : 14.9 ft.lb : 260 % : 300 % : F : 1.15 : 0.7188 sq.ft.lb			Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 21s (cold) 12s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 70.0 dB(A) : Direct On Line : 164 lb	
Output Efficiency (%) Power Factor	25% 89.3 0.53	89.5	75% 90.2 0.88	100% 90.2 0.91	Foundation loads Max. traction Max. compression	: 169 lb : 334 lb	
- OWEI FACIOI	0.00	0.00		e end	Non drive end	. 55 4 ID	
Bearing type		:	620)9 ZZ	6206 ZZ		
Sealing	: V'Ring V'Ring						
Lubrication interva		:		-	-		
Lubricant amount		:		-	-		
Lubricant type		:		Mo	obil Polyrex EM		

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary		Performed	Checked	Date
Performed by			,			,
Checked by					Page	Revision
Date	29/03/2024				1/1	