

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xec IE2 Three-Phase

Product code :

12384129

Catalog # :

E01536EP3YAX160MF3-W

Area classification : ZONA 2/22, GRUPO IIC/IIIB, T3(200 °C)/
T125 °C

Frame : 160M
Output : 15 kW (20 HP)
Poles : 2
Frequency : 50 Hz
Rated voltage : 380/660 V
Rated current : 28.5/16.4 A
L. R. Amperes : 200/115 A
LRC : 7.0
No load current : 8.60/4.95 A
Rated speed : 2940 rpm
Slip : 2.00 %
Rated torque : 36.0 ft.lb
Locked rotor torque : 240 %
Breakdown torque : 280 %
Insulation class : F
Service factor : 1.00
Moment of inertia (J) : 1.23 sq.ft.lb
Design : N

Locked rotor time : 14s (cold) 8s (hot)
Temperature rise : 80 K
Duty cycle : S1
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : B3T
Rotation¹ : Both (CW and CCW)
Noise level² : 67.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 306 lb

Output	25%		50%		75%		100%	
Efficiency (%)	91.6	90.8	91.4	91.0	91.3	91.3	90.9	91.3
	90.3	89.4	90.6	90.2	91.2	91.0	91.4	91.7
Power Factor	0.52	0.47	0.76	0.71	0.84	0.81	0.88	0.86
	0.44	0.45	0.67	0.68	0.78	0.80	0.84	0.86

Foundation loads
Max. traction : 374 lb
Max. compression : 681 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	10.0	9.5	9.4	9.0
	P2 (0,5;1,0)	8.9	8.5	8.4	8.1
	P3 (0,25;1,0)	7.9	7.6	7.5	7.2
	P4 (0,9;0,5)	4.4	4.2	4.2	4.0
	P5 (0,5;0,5)	3.1	2.9	2.9	2.8
	P6 (0,5;0,25)	1.8	1.7	1.7	1.6
	P7 (0,25;0,25)	1.3	1.2	1.2	1.2

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type :	6309 C3	6209 C3	
Sealing :	V'Ring	V'Ring	
Lubrication interval :	20000 h	20000 h	
Lubricant amount :	13 g	9 g	
Lubricant type :	Mobil Polyrex EM		

Notes:

EAC
TC RU C-BR.AA87.B.00977/22
2Ex ec IIC T3 Gc X
Ex tc IIIB T125°C Dc X
OOO «НАИО ЛЦБЭ»
IECEX
IECEX BAS 10.0099X
Ex ec IIC T3 Gc
Ex tc IIIB T125°C Dc

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	26/03/2024			
			Page 1 / 3	Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 3	Revision
Checked by					
Date	26/03/2024				

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	140 °C
2	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3		Revision
Checked by				
Date	26/03/2024			