

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Multimounting High Efficiency Three-Phase Product code : 13982722
Catalog # : .2512EP3EAL71-W22

Frame	: 71	Locked rotor time	: 19s (cold) 11s (hot)
Output	: 0.33 HP (0.25 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 380 V	Altitude	: 1000 m.a.s.l.
Rated current	: 1.04 A	Protection degree	: IP55
L. R. Amperes	: 3.64 A	Cooling method	: IC411 - TEFC
LRC	: 3.5	Mounting	: B3L(E)
No load current	: 0.750 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 880 rpm	Noise level ²	: 43.0 dB(A)
Slip	: 12.00 %	Starting method	: Direct On Line
Rated torque	: 1.97 ft.lb	Approx. weight ³	: 21.8 lb
Locked rotor torque	: 200 %		
Breakdown torque	: 200 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0228 sq.ft.lb		
Design	: N		

Output	25%	50%	75%	100%	Foundation loads					
Efficiency (%)	55.6	48.5	57.0	51.0	62.0	58.0	63.0	61.0	Max. traction	: 37 lb
	51.0		53.0		62.0		64.0			
Power Factor	0.22	0.19	0.37	0.33	0.48	0.42	0.58	0.51	Max. compression	: 58 lb
	0.18		0.31		0.41		0.49			

					<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:				6202 ZZ	6202 ZZ
Sealing	:				Oil Seal	Oil Seal
Lubrication interval	:				-	-
Lubricant amount	:				-	-
Lubricant type	:				Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	26/03/2024			
			Page	Revision
			1 / 1	