

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xdb IE2 Three-Phase

Product code : 12430233

Area classification : ZONA 1, GRUPO IIB, T4 (135 °C)

Catalog # : E09036XP3YAX280SMF3W

Frame	: 280S/M	Locked rotor time	: 45s (cold) 25s (hot)
Output	: 90 kW (125 HP)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 380/660 V	Altitude	: 1000 m.a.s.l.
Rated current	: 165/94.8 A	Protection degree	: IP56
L. R. Amperes	: 1152/663 A	Cooling method	: IC411 - TEFC
LRC	: 7.0	Mounting	: B3T
No load current	: 42.0/24.2 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 2975 rpm	Noise level <sup>2</sup>	: 77.0 dB(A)
Slip	: 0.83 %	Starting method	: Direct On Line
Rated torque	: 213 ft.lb	Approx. weight <sup>3</sup>	: 2053 lb
Locked rotor torque	: 180 %		
Breakdown torque	: 250 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 22.3 sq.ft.lb		
Design	: N		

Output	25%		50%		75%		100%		Foundation loads	
Efficiency (%)	94.1	93.7	94.0	93.8	94.6	94.6	94.4	94.6	Max. traction	: 485 lb
	93.4	91.5	93.5	92.4	94.5	93.6	94.5	94.5		
Power Factor	0.57	0.53	0.80	0.77	0.86	0.84	0.88	0.87	Max. compression	: 2538 lb
	0.49	0.52	0.74	0.76	0.82	0.84	0.86	0.87		

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	5.5	5.3	5.4	5.4
	P2 (0,5;1,0)	3.9	3.8	3.8	3.8
	P3 (0,25;1,0)	3.4	3.3	3.4	3.4
	P4 (0,9;0,5)	3.2	3.0	3.1	3.1
	P5 (0,5;0,5)	1.7	1.6	1.7	1.7
	P6 (0,5;0,25)	1.2	1.1	1.1	1.1
	P7 (0,25;0,25)	0.6	0.6	0.6	0.6

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6314 C3	6314 C3
Sealing	:	Viton Oil Seal	Viton Oil Seal
Lubrication interval	:	5000 h	5000 h
Lubricant amount	:	27 g	27 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

EAC  
EA3C RU C-BR.AA87.B.00379/20  
1Ex db IIB T4 Gb X  
ООО «НАННО ЛСВЭ»  
IECEX  
IECEX INE 16.0044X  
Ex db IIB T4 Gb

This revision replaces and cancel the previous one, which must be eliminated.

(1) Looking the motor from the shaft end.

(2) Measured at 1m and with tolerance of +3dB(A).

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	27/03/2024			

Page  
1 / 3  
Revision

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

(3) Approximate weight subject to changes after manufacturing process.  
(4) At 100% of full load.

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	27/03/2024				

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	150 °C

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3		Revision
Checked by				
Date	27/03/2024			