

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel JP Pump NEMA Premium
Efficiency Three-Phase

Product code : 12682721

Catalog # : 00158OT3E145JP-S

Frame : 143/5JP
Output : 1.5 HP (1.1 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 4.14/2.07 A
L. R. Amperes : 36.0/18.0 A
LRC : 8.7x(Code L)
No load current : 2.40/1.20 A
Rated speed : 1760 rpm
Slip : 2.22 %
Rated torque : 4.48 ft.lb
Locked rotor torque : 280 %
Breakdown torque : 330 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.1426 sq.ft.lb
Design : B

Locked rotor time : 27s (cold) 15s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 52.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 44.8 lb

Output	25%		50%		75%		100%	
Efficiency (%)	83.6	85.3	84.0	84.3	86.5	84.7	86.5	83.2
	83.1		83.0		84.7		84.2	
Power Factor	0.32	0.38	0.56	0.64	0.69	0.77	0.77	0.83
	0.32		0.57		0.70		0.79	

Foundation loads
Max. traction : 124 lb
Max. compression : 169 lb

	Drive end	Non drive end
Bearing type :	6206 ZZ	6203 ZZ
Sealing :	Without Bearing Seal	Without Bearing Seal
Lubrication interval :	-	-
Lubricant amount :	-	-
Lubricant type :	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/03/2024			

Page 1 / 1
Revision