## DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer	:						
Product line	: Multimounting IE3 Three-Phase		Product code : Catalog # :		13984002 .7518ET3WAL90S/L-W22		
Frame	: 90S/L	: 90S/L		rotor time	: 37s (cold) 21s (hot)		
Output	: 1 HP (0.75 kW)		Temperature rise		: 80 K		
Poles	: 4		Duty cycle		: S1		
	: <del>1</del> : 50 Hz		Ambient temperature		: -20°C to +40°C		
Frequency	: 220/380 V		Altitude			: 1000 m.a.s.l.	
Rated voltage						.S.I.	
Rated current	: 3.02/1.75 A		Protection degree		: IP55		
L. R. Amperes	: 19.3/11.2 A		Cooling method		: IC411 - TEFC		
LRC	: 6.4		Mounting		: B3L(E)		
No load current	: 1.64/0.950 A		Rotation <sup>1</sup>		: Both (CW and CCW)		
Rated speed	: 1445 rpm		Noise level <sup>2</sup>		: 49.0 dB(A)		
Slip	: 3.67 %		Starting method		: Direct On Line		
Rated torque	: 3.63 ft.lb		Approx. weight <sup>3</sup>		: 34.4 lb	0	
Locked rotor torque			πρρίοχ	. Worgin	. 04.4 10		
Breakdown torque							
Insulation class	: F						
Service factor	: 1.25						
Moment of inertia		sq.ft.lb					
Design	: N						
O t t	050/ 500/	750/ 4000/	C				
Output	25% 50%	75% 100%	Foundation				
Efficiency (%)		79.2 82.0 80.0 82.5 82.0 82.5 82.5   Max. traction : 76 I		: 76 lb			
	78.4 80.0 84.0 85.5		1				
Power Factor	0.34 0.28 0.58 0.50 0.71 0.63 0.79 0.73		Max. compression		: 110 lb		
		0.65 0.74					
Losses at normative	ve operating points (sp						
	P1 (0,9;1,0)	19.7	19	9.7	17.7		
	P2 (0,5;1,0)	15.6	1:	5.6	14.0		
	P3 (0,25;1,0)	15.3	15	5.3	13.7		
Losses (%)	P4 (0,9;0,5)	12.7		2.7	11.4		
200000 (70)	P5 (0,5;0,5)	8.6		3.6	7.7		
		7.2		7.2	6.4		
	P6 (0,5;0,25)						
	P7 (0,25;0,25)	5.3	5	5.3	4.7		
		Drive end		Non drive end			
Bearing type	:	6205 ZZ		6204 ZZ			
Sealing	:	V'Ring		V'Ring			
Lubrication interv	al ·	-	• · · · · · · · · · · · · · · · · · · ·				
Lubricant amount		_		_			
Lubricant type	•	Mol	bil Polyrex	ΕM			
Lubricant type	•	IVIO	Oli i Olyicx	LIVI			
Notes:							
This revision replaces and cancel the previous one, which must be eliminated.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA				
	otor from the shaft end.		MG-1.				
(2) Measured at 1m and with tolerance of +3dB(A).							
	eight subject to change						
manufacturing pro							
(4) At 100% of full							
. ,				I			
Rev.	Chang	ges Summary		Performed	Checked	Date	
		·					

	Changes Summary	Performed	Checked	Date
			Page	Revision
26/03/2024			1/1	
	26/03/2024	26/03/2024	26/03/2024	Page