

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xdb IE2 Three-Phase

Product code : 12430452
Catalog # : E00412XP3YAX132MF3-W

Area classification : ZONA 1, GRUPO IIB, T4 (135 °C)

Frame	: 132S/M	Locked rotor time	: 37s (cold) 21s (hot)
Output	: 4 kW (5.5 HP)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 380/660 V	Altitude	: 1000 m.a.s.l.
Rated current	: 9.71/5.59 A	Protection degree	: IP56
L. R. Amperes	: 53.4/30.7 A	Cooling method	: IC411 - TEFC
LRC	: 5.5	Mounting	: B3T
No load current	: 4.70/2.71 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 960 rpm	Noise level ²	: 53.0 dB(A)
Slip	: 4.00 %	Starting method	: Direct On Line
Rated torque	: 29.4 ft.lb	Approx. weight ³	: 234 lb
Locked rotor torque	: 170 %		
Breakdown torque	: 200 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 1.07 sq.ft.lb		
Design	: N		

Output	25%		50%		75%		100%		Foundation loads	
Efficiency (%)	85.0	83.7	84.9	84.0	85.0	84.8	84.6	84.8	Max. traction	: 277 lb
	82.3	82.8	83.0	84.0	84.4	86.5	84.9	87.5		
Power Factor	0.33	0.30	0.55	0.51	0.68	0.64	0.74	0.72	Max. compression	: 511 lb
	0.27	0.28	0.47	0.48	0.61	0.61	0.69	0.69		

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6308 ZZ	6207 ZZ
Sealing	:	Oil Seal	Lip Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

EAC
EA3C RU C-BR.AA87.B.00379/20
1Ex db IIB T4 Gb X
ООО «НАННО ЦСВЭ»
IECEX
IECEX INE 22.0044X
Ex db IIB T4 Gb

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	27/03/2024			

Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	150 °C

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date	27/03/2024				