

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xec IE2 Three-Phase

Product code : 13876568

Area classification : ZONA 2/22, GRUPO IIC/IIIB, T3(200 °C)/
T125 °C

Catalog # : E0.3718EP3WAX71F3-W2

Frame : 71
Output : 0.37 kW (0.5 HP)
Poles : 4
Frequency : 50 Hz
Rated voltage : 220/380 V
Rated current : 1.76/1.02 A
L. R. Amperes : 7.22/4.18 A
LRC : 4.1
No load current : 1.12/0.650 A
Rated speed : 1370 rpm
Slip : 8.67 %
Rated torque : 1.90 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 200 %
Insulation class : F
Service factor : 1.00
Moment of inertia (J) : 0.0183 sq.ft.lb
Design : N

Locked rotor time : 86s (cold) 48s (hot)
Temperature rise : 80 K
Duty cycle : S1
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : B3T
Rotation¹ : Both (CW and CCW)
Noise level² : 43.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 25.4 lb

Output	25%		50%		75%		100%	
Efficiency (%)	62.5	59.3	66.0	63.0	68.5	68.0	72.7	72.7
	59.3	58.2	63.0	62.0	68.0	67.0	72.7	72.0
Power Factor	0.33	0.29	0.55	0.50	0.66	0.62	0.76	0.72
	0.27	0.28	0.46	0.48	0.58	0.60	0.69	0.68

Foundation loads
Max. traction : 32 lb
Max. compression : 57 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	44.8	44.8	44.8	46.4
	P2 (0,5;1,0)	39.0	39.0	39.0	40.3
	P3 (0,25;1,0)	37.5	37.5	37.5	38.8
	P4 (0,9;0,5)	27.5	27.5	27.5	28.8
	P5 (0,5;0,5)	18.9	18.9	18.9	19.8
	P6 (0,5;0,25)	15.5	15.5	15.5	16.3
	P7 (0,25;0,25)	10.9	10.9	10.9	11.4

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6202 ZZ	6202 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

ATEX
Baseefa 10ATEX0192X
BAS21UKEX0284X
II 3G Ex ec IIC T3 Gc
II 3D Ex tc IIIB T125°C Dc
EAC
TC RU C-BR.AA87.B.00977/22
2Ex ec IIC T3 Gc X
Ex tc IIIB T125°C Dc X
ООО «НАИНО ЛЦБЭ»
IECEX
IECEX BAS 10.0099X

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 3 Revision		
Checked by				
Date	26/03/2024			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Ex ec IIC T3 Gc
Ex tc IIIB T125°C Dc

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 3	Revision
Checked by					
Date	26/03/2024				

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	140 °C
2	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by					
Date	26/03/2024				
				3 / 3	