

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xec IE2 Three-Phase

Product code : 12381619
Catalog # : E00318EP3WAX100LF3-W

Area classification : ZONA 2/22, GRUPO IIC/IIIB, T3(200 °C)/T125 °C

Frame : 100L
Output : 3 kW (4 HP)
Poles : 4
Frequency : 50 Hz
Rated voltage : 220/380 V
Rated current : 11.1/6.42 A
L. R. Amperes : 72.1/41.7 A
LRC : 6.5
No load current : 4.92/2.85 A
Rated speed : 1410 rpm
Slip : 6.00 %
Rated torque : 15.0 ft.lb
Locked rotor torque : 280 %
Breakdown torque : 260 %
Insulation class : F
Service factor : 1.00
Moment of inertia (J) : 0.2307 sq.ft.lb
Design : N

Locked rotor time : 25s (cold) 14s (hot)
Temperature rise : 80 K
Duty cycle : S1
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : B3T
Rotation¹ : Both (CW and CCW)
Noise level² : 53.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 76.6 lb

Output	25%	50%	75%	100%				
Efficiency (%)	0.000	85.4	85.0	85.5	85.6			
	0.000	84.3	84.0	85.5	86.5			
	0.000							
Power Factor	0.00	0.00	0.65	0.60	0.77	0.73	0.83	0.81
	0.00		0.56	0.56	0.70	0.69	0.78	0.78

Foundation loads
Max. traction : 323 lb
Max. compression : 400 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	17.6	17.4	16.9	14.8
	P2 (0,5;1,0)	17.3	17.2	16.6	14.6
	P3 (0,25;1,0)	15.2	15.1	14.6	12.8
	P4 (0,9;0,5)	6.9	6.8	6.6	5.8
	P5 (0,5;0,5)	5.5	5.5	5.3	4.7
	P6 (0,5;0,25)	3.2	3.2	3.1	2.7
	P7 (0,25;0,25)	2.5	2.5	2.4	2.1

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6206 ZZ	6205 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

EAC
TC RU C-BR.AA87.B.00977/22
2Ex ec IIC T3 Gc X
Ex tc IIIB T125°C Dc X
ООО «НАННО ЛСВЭ»
IECEX
IECEX BAS 10.0099X
Ex ec IIC T3 Gc
Ex tc IIIB T125°C Dc

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 3		
Checked by				
Date	27/03/2024			
			Revision	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	27/03/2024				

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	140 °C
2	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3		Revision
Checked by				
Date	27/03/2024			