

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xec IE2 Three-Phase

Product code : 14427904

Area classification : ZONA 2/22, GRUPO IIC/IIIB, T3(200 °C)/
T125 °C

Catalog # : E15012EP3YAX355MLF3W

Frame : 355M/L
Output : 150 kW (200 HP)
Poles : 6
Frequency : 50 Hz
Rated voltage : 380/660 V
Rated current : 297/171 A
L. R. Amperes : 1604/923 A
LRC : 5.4
No load current : 120/69.1 A
Rated speed : 992 rpm
Slip : 0.80 %
Rated torque : 1070 ft.lb
Locked rotor torque : 160 %
Breakdown torque : 200 %
Insulation class : F
Service factor : 1.00
Moment of inertia (J) : 176 sq.ft.lb
Design : N

Locked rotor time : 63s (cold) 35s (hot)
Temperature rise : 80 K
Duty cycle : S1
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : B3T
Rotation¹ : Both (CW and CCW)
Noise level² : 73.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 2956 lb

Output	25%		50%		75%		100%	
Efficiency (%)	94.4	93.7	94.5	94.2	94.8	94.5	94.8	95.0
	93.2	93.0	93.8	93.4	94.4	94.7	95.0	95.0
Power Factor	0.43	0.39	0.69	0.64	0.77	0.74	0.81	0.79
	0.36	0.36	0.61	0.59	0.71	0.71	0.76	0.77

Foundation loads
Max. traction : 3122 lb
Max. compression : 6077 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	5.4	5.2	5.2	5.2
	P2 (0,5;1,0)	4.0	3.9	3.9	3.9
	P3 (0,25;1,0)	3.4	3.2	3.2	3.2
	P4 (0,9;0,5)	3.2	3.1	3.1	3.1
	P5 (0,5;0,5)	2.0	1.9	1.9	1.9
	P6 (0,5;0,25)	1.5	1.5	1.5	1.5
	P7 (0,25;0,25)	0.9	0.9	0.9	0.9

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6322 C3	6319 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	13000 h	16000 h
Lubricant amount	:	60 g	45 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

EAC
TC RU C-BR.AA87.B.00977/22
2Ex ec IIC T3 Gc X
Ex tc IIIB T125°C Dc X
ООО «НАИО ЛЦБЭ»
IECEX
IECEX BAS 10.0099X
Ex ec IIC T3 Gc
Ex tc IIIB T125°C Dc

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 3		
Checked by				
Date	26/03/2024			
			Revision	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 3	Revision
Checked by					
Date	26/03/2024				

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	140 °C
2	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3		Revision
Checked by				
Date	26/03/2024			