

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xec IE2 Three-Phase

Product code : 14351880

Area classification : ZONA 2/22, GRUPO IIC/IIIB, T3(200 °C)/
T125 °C

Catalog # : E03712EP3YAX250SMF3W

Frame : 250S/M
Output : 37 kW (50 HP)
Poles : 6
Frequency : 50 Hz
Rated voltage : 380/660 V
Rated current : 72.6/41.8 A
L. R. Amperes : 450/259 A
LRC : 6.2
No load current : 27.0/15.5 A
Rated speed : 985 rpm
Slip : 1.50 %
Rated torque : 265 ft.lb
Locked rotor torque : 210 %
Breakdown torque : 250 %
Insulation class : F
Service factor : 1.00
Moment of inertia (J) : 26.2 sq.ft.lb
Design : N

Locked rotor time : 28s (cold) 16s (hot)
Temperature rise : 80 K
Duty cycle : S1
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : B3T
Rotation¹ : Both (CW and CCW)
Noise level² : 64.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 966 lb

Output	25%		50%		75%		100%	
Efficiency (%)	92.1	92.1	92.2	92.2	92.2	92.2	92.2	92.2
	92.0	92.3	92.1	92.4	92.2	93.0	92.2	93.0
Power Factor	0.46	0.42	0.72	0.68	0.81	0.78	0.84	0.83
	0.38	0.40	0.65	0.66	0.76	0.77	0.81	0.82

Foundation loads
Max. traction : 1558 lb
Max. compression : 2524 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	8.2	8.2	8.2	7.3
	P2 (0,5;1,0)	6.9	6.9	6.9	6.1
	P3 (0,25;1,0)	6.2	6.2	6.2	5.5
	P4 (0,9;0,5)	3.8	3.8	3.8	3.3
	P5 (0,5;0,5)	2.6	2.6	2.6	2.3
	P6 (0,5;0,25)	1.7	1.7	1.7	1.5
	P7 (0,25;0,25)	1.1	1.1	1.1	1.0

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6314 C3	6314 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	20000 h	20000 h
Lubricant amount	:	27 g	27 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

EAC
TC RU C-BR.AA87.B.00977/22
2Ex ec IIC T3 Gc X
Ex tc IIIB T125°C Dc X
ООО «НАИО ЛЦБЭ»
IECEX
IECEX BAS 10.0099X
Ex ec IIC T3 Gc
Ex tc IIIB T125°C Dc

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 3		
Checked by				
Date	27/03/2024			
			Revision	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 3	Revision
Checked by					
Date	27/03/2024				

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	140 °C
2	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3		Revision
Checked by				
Date	27/03/2024			