

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Jet Pump - J type Standard
Efficiency Three-Phase

Product code : 12676615

Catalog # : 00136OS3HJP56J-S

Frame : 56J
Output : 1 HP (0.75 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 575 V
Rated current : 1.23 A
L. R. Amperes : 7.88 A
LRC : 6.4x(Code J)
No load current : 0.760 A
Rated speed : 3470 rpm
Slip : 3.61 %
Rated torque : 1.51 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 250 %
Insulation class : F
Service factor : 1.40
Moment of inertia (J) : 0.0517 sq.ft.lb

Locked rotor time : 41s (cold) 23s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : CCW
Noise level² : 62.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 22.1 lb

Output	25%	50%	75%	100%
Efficiency (%)	68.4	70.0	74.0	75.5
Power Factor	0.34	0.60	0.73	0.81

Foundation loads
Max. traction : 26 lb
Max. compression : 48 lb

	Drive end	Non drive end
Bearing type	6203 2RS	6202 2RS
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 1		
Checked by				
Date	27/03/2024			