

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xdb IE3 Three-Phase

Product code : 12383806

Area classification : ZONA 1, GRUPO IIB, T4 (135 °C)

Catalog # : E03018XT3YAX200LF3-W

Frame	: 200M/L	Locked rotor time	: 16s (cold) 9s (hot)
Output	: 30 kW (40 HP)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 380/660 V	Altitude	: 1000 m.a.s.l.
Rated current	: 58.0/33.4 A	Protection degree	: IP56
L. R. Amperes	: 423/244 A	Cooling method	: IC411 - TEFC
LRC	: 7.3	Mounting	: B3T
No load current	: 24.5/14.1 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1480 rpm	Noise level ²	: 63.0 dB(A)
Slip	: 1.33 %	Starting method	: Direct On Line
Rated torque	: 143 ft.lb	Approx. weight ³	: 777 lb
Locked rotor torque	: 250 %		
Breakdown torque	: 280 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 7.60 sq.ft.lb		
Design	: N		

Output	25%	50%	75%	100%	Foundation loads					
Efficiency (%)	93.3	92.7	93.4	92.9	93.6	93.6	93.6	93.6	Max. traction	: 1195 lb
	91.9	92.1	92.3	92.6	93.3	93.7	93.6	94.1		
Power Factor	0.42	0.38	0.68	0.63	0.79	0.75	0.84	0.81	Max. compression	: 1982 lb
	0.35	0.36	0.59	0.62	0.72	0.74	0.79	0.80		

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	6.6	6.6	6.6	6.1
	P2 (0,5;1,0)	5.8	5.8	5.8	5.3
	P3 (0,25;1,0)	5.5	5.5	5.5	5.0
	P4 (0,9;0,5)	3.1	3.1	3.1	2.8
	P5 (0,5;0,5)	2.3	2.3	2.3	2.1
	P6 (0,5;0,25)	1.5	1.5	1.5	1.4
	P7 (0,25;0,25)	1.1	1.1	1.1	1.0

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6312 C3	6212 C3
Sealing	:	Oil Seal	Lip Seal
Lubrication interval	:	20000 h	20000 h
Lubricant amount	:	21 g	13 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

ATEX
 INERIS 22ATEX0025X
 CML 23UKEX1256X
 II 2G Ex db IIB T4 Gb
 EAC
 EAЭC RU C-BR.AA87.B.00379/20
 1Ex db IIB T4 Gb X
 ООО «НАННО ЦСВЭ»
 IECEX
 IECEX INE 22.0044X
 Ex db IIB T4 Gb

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 3		
Checked by				
Date	27/03/2024			
			Revision	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

Subject to change without notice

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 3	Revision
Checked by					
Date	27/03/2024				

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	150 °C

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3		Revision
Checked by				
Date	27/03/2024			