

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IE2 Three-Phase

Product code : 14424386
Catalog # : E09036EP3Y280SMF3-W2

Frame	: 280S/M	Locked rotor time	: 45s (cold) 25s (hot)
Output	: 90 kW (125 HP)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 380/660 V	Altitude	: 1000 m.a.s.l.
Rated current	: 165/95.0 A	Protection degree	: IP55
L. R. Amperes	: 1155/665 A	Cooling method	: IC411 - TEFC
LRC	: 7.0	Mounting	: B3T
No load current	: 42.0/24.2 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 2975 rpm	Noise level ²	: 77.0 dB(A)
Slip	: 0.83 %	Starting method	: Direct On Line
Rated torque	: 213 ft.lb	Approx. weight ³	: 1643 lb
Locked rotor torque	: 180 %		
Breakdown torque	: 250 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 22.3 sq.ft.lb		
Design	: N		

Output	25%		50%		75%		100%		Foundation loads	
Efficiency (%)	94.3	93.9	94.2	94.0	94.6	94.6	94.4	94.6	Max. traction	: 690 lb
	93.7	91.5	93.8	92.4	94.5	93.6	94.5	94.5		
Power Factor	0.58	0.53	0.81	0.77	0.86	0.85	0.88	0.87	Max. compression	: 2333 lb
	0.49	0.52	0.74	0.76	0.82	0.84	0.86	0.87		

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	5.5	5.3	5.4	5.4
	P2 (0,5;1,0)	3.8	3.7	3.8	3.8
	P3 (0,25;1,0)	3.3	3.2	3.3	3.3
	P4 (0,9;0,5)	3.1	3.0	3.1	3.1
	P5 (0,5;0,5)	1.6	1.6	1.6	1.6
	P6 (0,5;0,25)	1.1	1.1	1.1	1.1
	P7 (0,25;0,25)	0.6	0.6	0.6	0.6

		Drive end	Non drive end
Bearing type	:	6314 C3	6314 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	5000 h	5000 h
Lubricant amount	:	27 g	27 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	26/03/2024			
			Page	Revision
			1 / 2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by					
Date	26/03/2024			2 / 2	